

POYAD SB131

Polypropylene

Pooya Polymer Tehran

Описание материалов:

Slip / Anti-block MB

Description

POYAD SB131 is a PP based master batch containing a blend of a migration slip agent and a special anti block agent. It's designed for use in manufacturing of cast and blown PP film and sheet where the end product requires slip and anti-block characteristics.

The slip additive migrates to the film/sheet surface relatively slowly, thus reducing potential problems during sealing and printing. Due to its specialized anti-block it has almost no effect on haze and gloss.

Application

POYAD SB131 is designed for ease of dilution and homogeneous mixing and is therefore suitable for direct addition using automatic dosing units or by pre-blending. Depending on the film/sheet thickness (the thicker film needs less addition level), extrusion condition, application and existence of other additives it can be used from 0.5 to 2%.

| Главная Информация | | | |
|---------------------------|----------------------|---------------------|-----------------|
| Добавка | Антиблок | | |
| | Комбинация | | |
| Характеристики | Антиблокировка | | |
| | Комбинация | | |
| Используется | Пленка | | |
| | Маточная смесь | | |
| | Лист | | |
| Формы | Гранулы | | |
| Физический | Номинальное значение | Единица измерения | Метод испытания |
| Moisture Content | < 1000 | ppm | ASTM D644 |
| Дополнительная информация | Номинальное значение | Единица измерения | Метод испытания |
| Дисперсия | OK | | Internal Method |
| Pellet Size | 30.0 to 40.0 | pcs/cm ³ | Internal Method |

* Отказ от ответственности: Информация на этой странице предоставлена производителем, и поставщик документа не несет никакой юридической ответственности. Все права защищены. Пожалуйста, немедленно свяжитесь с нами в случае каких-либо нарушений.

Свяжитесь с нами

Susheng Import & Export Trading Co.,Ltd.

Телефон: +86-021-58958519

Мобильный телефон: +86-13424755533

Email: sales@su-jiao.com

Адрес: Господин Чжао

Район Фэнсянь, Шанхай, Китай

